

# Leica FlexLine TS07 Manual Total Station



FlexLine



## LEICA FLEXLINE TS07 MANUAL TOTAL STATION

- **Work faster:** measure more points per day due to faster measurement and stakeout procedures (endless drives, trigger key, drives on both sides, pinpoint EDM and more), supported by our comprehensive and user-friendly Leica FlexField software.
- **Use it trouble-free:** increase productivity and minimise downtime by relying on instruments that simply work and come with a global service and support network.
- **Choose products that are built to last:** FlexLine operates with the same high level of quality even after years of use under harsh conditions (like mud, dust, blowing rain, extreme heat and cold).
- **Control your investment:** reliability, speed and accuracy ensure a lower investment over the product lifetime and a higher resell value.
- **Save time with AutoHeight:** measure, read and set the instrument height automatically with this revolutionary feature (optional). Errors are minimised and the setup process onsite is faster.

The Leica FlexLine TS07 high-quality, manual total station is based on a proven product concept that has been revolutionising the world of measurement and survey for nearly 200 years. The instrument is equipped with a comprehensive application-based software package - Leica FlexField software - that enables most survey and stakeout tasks to be carried out easily and efficiently. The new FlexLine manual total stations work reliably and deliver accurate results even in harsh environments.

leica-geosystems.com



- when it has to be **right**

**Leica**  
Geosystems

# Leica FlexLine TS07



Leica FlexLine TS07

## ANGULAR MEASUREMENT

Accuracy HZ and V	Absolute, continuous, diametrical <sup>1</sup> <ul style="list-style-type: none"> <li>■ Display resolution: 0.1" (0.1 mgon)</li> <li>■ Quadruple axis compensation</li> <li>■ Compensator setting accuracy<sup>2</sup>: 0.5" / 1" / 1.5" / 2"</li> <li>■ Compensator range: +/- 4'</li> <li>■ Electronic level resolution: 2"</li> <li>■ Circular level sensitivity: 6' / 2 mm</li> </ul>	1" / 2" / 3" / 5" / 7"	✓
-------------------	---	------------------------	---

## DISTANCE MEASUREMENT

Range	<ul style="list-style-type: none"> <li>■ Prism (GPR1, GPH1P): 1.5 m to 3.500 m</li> <li>■ Prism GPR1 (Long Range mode) &gt; 10.000 m</li> </ul>		✓
	<ul style="list-style-type: none"> <li>■ Non-Prism / Any surface</li> <li>■ R500<sup>3</sup></li> <li>■ R1000<sup>4</sup></li> </ul>		✓
Accuracy / Measurement time	<ul style="list-style-type: none"> <li>■ Single prism</li> <li>■ 1 mm + 1.5 ppm (typical 1 - 2 s)</li> </ul>		✓
	<ul style="list-style-type: none"> <li>■ Non-Prism / Any surface</li> <li>■ 0 m - 500 m: 2 mm + 2 ppm (typical 3 - 6 s)</li> <li>■ &gt; 500 m: 4 mm + 2 ppm (typical 3 - 6 s)</li> </ul>		✓
	Display resolution: 0.1 mm		✓
Laser dot size	<ul style="list-style-type: none"> <li>■ At 30 m: 7 mm x 10 mm</li> <li>■ At 50 m: 8 mm x 20 mm</li> <li>■ At 100 m: 16 mm x 25 mm</li> </ul>		✓
Telescope	<ul style="list-style-type: none"> <li>■ Magnification: 30x</li> <li>■ Resolving power: 3"</li> <li>■ Focusing range: 1.55 m / 5.08 ft to infinity</li> <li>■ Field of view: 1°30' / 1.66 gon / 2.7 m at 100 m</li> </ul>		✓

## GENERAL

Display and keyboard		3.5" (inch), 320 x 240 px QVGA, colour, touch, 28 keys <sup>5b</sup>	
	2 <sup>nd</sup> keyboard		•
	Key illumination		✓
Operation	<ul style="list-style-type: none"> <li>■ Endless drives for HZ &amp; V</li> <li>■ Trigger-Key: user definable with 2 functions</li> </ul>		✓
Power management	<ul style="list-style-type: none"> <li>■ Exchangeable Lithium-Ion battery<sup>6</sup></li> <li>■ Operating time with GEB361</li> <li>■ Operating time with GEB331</li> </ul>		up to 30 h up to 15 h
	<ul style="list-style-type: none"> <li>■ External supply voltage</li> <li>■ Nominal voltage 13.0 V DC &amp; 16 W max</li> </ul>		✓
Data storage	<ul style="list-style-type: none"> <li>■ Internal memory: 2 GB Flash</li> <li>■ Memory card: SD card 1 GB or 8 GB</li> <li>■ USB memory stick: 1 GB</li> </ul>		✓
Processor	<ul style="list-style-type: none"> <li>■ TI OMAP4430 1GHz Dual-core ARM® Cortex™ A9 MPCore™</li> <li>■ Operating system – Windows EC7</li> </ul>		✓
Interfaces	<ul style="list-style-type: none"> <li>■ RS232<sup>7</sup>, USB device</li> <li>■ Bluetooth®<sup>8</sup>, WLAN<sup>9</sup></li> <li>■ Mobile Data sidecover: LTE-Modem for internet access</li> </ul>		✓ ✓ •
Guide Light (EGL)	<ul style="list-style-type: none"> <li>■ Working range: 5 m to 150 m</li> <li>■ Position accuracy: 5 cm at 100 m</li> <li>■ Wavelength red /orange: 617 nm / 593 nm</li> </ul>		✓ (R1000)
Laser plummet (Laserclass 2)	<ul style="list-style-type: none"> <li>■ Accuracy</li> <li>■ Plumb line deviation: 1.5 mm at 1.5 m instrument height</li> <li>■ Diameter of laser point: 2.5 mm at 1.5 m instrument height</li> </ul>		✓
AutoHeight module for automatic instrument height measurement (Laserclass 2)	<ul style="list-style-type: none"> <li>■ Accuracy</li> <li>■ Distance accuracy: 1.0 mm (1 Sigma)</li> <li>■ Distance range: 0.7 m to 2.7 m</li> </ul>		•
Weight			4.3 - 4.5 kg
Environmental specifications <sup>10</sup>	<ul style="list-style-type: none"> <li>■ Working temperature range: -20°C to +50°C</li> <li>■ Arctic version: -35°C to +50°C</li> <li>■ Dust / Water (IEC 60529) / Humidity: IP66 / 95%, non-condensing</li> <li>■ Military Standard 810G, Method 506.5</li> </ul>		✓ • ✓ ✓

### Legend:

1. 1" (0.3 mgon), 2" (0.6 mgon), 3" (1 mgon), 5" (1.5 mgon), 7" (2 mgon)
2. Angular accuracy / Compensator setting accuracy: 1" / 0.5" (0.2 mgon), 2" / 0.5" (0.2 mgon), 3" / 1.0" (0.3 mgon), 5" / 1.5" (0.5 mgon), 7" / 2.0" (0.7 mgon)
3. R500: Kodak gray 90% reflective (1.5 m to >500 m), Kodak gray 18% reflective (1.5 m to >200 m)
4. R1000: Kodak gray 90% reflective (1.5 m to >1000 m), Kodak gray 18% reflective (1.5 m to >500 m)
5. (a) Face I standard, (b) Face I standard, face II optional

6. Distance/angle measurement every 30 seconds
7. 5 PIN Lemo-0 for power, communication and data transfer
8. For communication and data transfer
9. For internet access, communication and data transfer, WLAN range up to 200 m
10. Storage temperature: -40°C to +70°C

✓ = Included • = Optional ✗ = Not available

Laser radiation, avoid direct eye exposure.  
Class 3R laser product in accordance with IEC 60825-1:2014.

The Bluetooth® trademarks are owned by Bluetooth SIG, Inc. Windows is a registered trademark of Microsoft Corporation. Other trademarks and trade names are those of their respective owners.

Copyright Leica Geosystems AG, 9435 Heerbrugg, Switzerland. All rights reserved. Leica Geosystems AG is part of Hexagon AB. 01.19



**Leica Geosystems AG**  
Heinrich-Wild-Strasse  
9435 Heerbrugg, Switzerland  
+41 71 727 31 31

- when it has to be **right**

**Leica**  
Geosystems